


Revision				
Rev.	Explanation	Date	Revised by	Approved by



Index	Name	L	Tolerance	Lg	Tolerance	Surface [dm2]	Weight [g]
320608	CT 6x80	80	± 2	50	± 2,5	0,21	12,1
	CT 6x90	90				0,22	13,1
320610	CT 6x100	100	± 2,5	60	±3	0,23	13,3
320612	CT 6x120	120	± 3	80	±4	0,27	15,3
320614	CT 6x140	140	± 3,5			0,29	17,6
320616	CT 6x160	160	± 4			0,32	19,9
320618	CT 6x180	180	± 4,5			0,35	22,2
320620	CT 6x200	200	± 5			0,38	24,6
320622	CT 6x220	220	± 5,5			0,40	26,9
320624	CT 6x240	240	± 6			0,43	29,2
320626	CT 6x260	260	± 6,5			0,46	31,5
320628	CT 6x280	280	± 7			0,49	33,8
320630	CT 6x300	300	± 7,5			0,51	36,1



Note:

1. Tolerancje ogólne wg. EN 22768 mK.
2. Powłoka Fe/ZN 12c wg. EN ISO 2081

Design		D. Kozłowski		Checked				Approved		-		Note					
Drawn		D.Kozłowski		Format		A4		Scale		1:1		Material		Pręt Ø4.35 - 20MnB4			
Date		16.10.2023		Screw DMX CT 6													
Title																Sheet 1 / 1	
Logo				-												Rev A	
Company		DOMAX Sp. z o.o.		DMX CT 6													